



# Axwood Passthrough Dishwasher 3 phase - PTD-601D

#### **Quick Overview**

## Axwood Pass-Through Dishwasher - Hood Type Dishwasher - PTD-601D

- Easy to use: Easy installation and service
- User- friendly one touch system
- High Performance: Powerful wash pump deliver higher volumes of wash water and ensures faster clean up times.
- Low running costs: Hi- tech computer controller ensures low water, low energy and less detergent consumption.
- Quality: Full stainless steel structure with stainless steel wash & rinse arms.
- Incoming water temperature 10-60°C
- WaterMark approved

#### **Description**

#### Axwood Pass-Through Dishwasher - Hood Type Dishwasher - PTD-601D

- Easy to use: Easy installation and service
- User- friendly one-touch system
- **High Performance:** Powerful wash pump delivers higher volumes of wash water and ensures faster clean up times.
- Low running costs: Hi-tech computer controller ensures low water, low energy, and less detergent consumption.
- Quality: Full stainless steel structure with stainless steel wash & rinse arms.
- Incoming water temperature 10-60°C
- · Rated currently of air circuit breaker 40A
- Record the number of washing 9999
- 60 racks per hour
- Drain outlet 42mm
- WaterMark approved

#### **Specifications**

Net Weight: 104kg

• Dimensions (WxDxH): 710 x 790 x 1430 ± 20 mm

• Door Entry: 400mm

• Basket Size: 500 x 500mm

• Electrical Supply (V/Hz/ph): N?415V AC / 50Hz / 3ph

• Cycle Length(3wash cycles): 60 / 90 / 120 sec

#### Wash Pump, Tank and Element

Wash Pump: 3-ph:400 L/min, 0.6 Kw
Wash Tank Capacity: 27 Litres

• Wash Tank Heater: 3.0 Kw

Wash temperature: 60°C to 65°C

#### Rinse Pump, Tank and Element

• Rinse Pump: 0.35 Kw

• Rinse Tank Capacity: 11 Litres

Rinse Tank Heater: 9Kw

• Rinse Temperature: 82°C minimum

• Water Consumption: 2.9 Litres per cycle

#### **Electrical and Water Connections:**

Electrical Input: 415V / 50Hz / 3ph, 15.71Kw
Water Input: 15 °Cminimum @ 100-400kPa

• Hot Water Inlet: 3/4" B.S.P. fitting

• Drain Outlet:11/2" B.S.P. gravity fed

#### 1 Year Parts and Labour Warranty

### **Your Shipping Specifications**

Net Weight (Kg)	104
Width (mm)	710
Depth (mm)	790
Height (mm)	1430
Packing Width (mm)	850
Packing Depth (mm)	745
Packing Height (mm)	1600
Power	415V / 50Hz / 3ph, 15.71Kw